



1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Vinyl Bumper Guards

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction** Tarkett Resilient Vinyl Corner Bumper Guards are manufactured from a homogeneous composition vinyl polymer, high quality additives, and colorants. Both formulations exceed ASTM E 648 Class 1 Flammability requirements. Tarkett Corner Bumper Guards are designed for interior applications only.

1.3.2. **Styles:**

VBG-XX: 90° angular shaped profile with 2-3/8" (6.03cm) return legs. Legs taper from 5/16" (7.94mm) at nose to 1/16" (1.57mm) at tip

VBG-XX-A: 90° angular shaped profile with 1-1/2" (3.81cm) return legs, 1/8" (3.18mm) leg thickness

VBG-XX-B: 90° angular shaped profile with 3/4" (1.91cm) return legs, 1/8" (3.18mm) leg thickness

VBG-XX-C: 90° angular shaped profile with 1-1/4" (3.18cm) return legs, 1/4" (6.35mm) leg thickness

1.3.3. **Physical Characteristics:**

Lengths / Packaging:

VBG-XX, VBG-XX-A, and VBG-XX-B: 4 ft (1.22m) lengths and 8 ft (2.44 m) lengths - 8 lengths per carton

VBG-XX-C: 8 ft. (2.44 m) lengths - 10 lengths per carton

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations of .5 for flat surfaces

2.2. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

3. INSTALLATION

3.1. See Tarkett Resilient Moulding installation and maintenance instructions for complete details.

3.2. **Adhesives:**

946 Premium Contact Adhesive

Application: Brush or roller

Approximate coverage:

1 Quart (0.95 liters) – 24 to 36 sq. ft.

1 Gallon (3.79 liters) – 100 to 150 sq. ft.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Resilient Moulding Installation & Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916 Ext. 9297 Fax 440.632.5643
info@tarkettna.com

www.tarkettna.com