

Vinyl Nosings

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** : Resilient Vinyl Stair Nosings

1.1. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkett.com

1.2. **Proprietary Product Description:**

1.2.1. **Construction:** Tarkett Vinyl Stair Nosings are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants to meet the performance requirements of ASTM F-2169 Standard Specification for Resilient Stair Treads, Type TV, Class 1 and 2, Group 1 and 2. Tarkett Vinyl Stair Nosings are available with a 2" (5.08 cm) wide co-extruded strip of contrasting color. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Tarkett Vinyl Stair Nosings are designed for interior applications only and not recommended for commercial kitchen environments.

1.2.2. **Styles, Physical Characteristics, & Packaging:**

(See table on pages 2 & 3)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Hardness** (ASTM D 2240): Not less than 85 Shore A
- 2.2. **Abrasion Resistance** (ASTM D 3389): < 1 gram weight loss
- 2.3. **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations of .6 for flat surfaces
- 2.4. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

3. INSTALLATION

3.1. See Vinyl Nosing installation instructions for complete details.

3.2. **Adhesives:**

- **Tarkett 946 Premium Contact Adhesive Coverage:**
Non-porous Substrate:
1 quart unit (0.95 liters) – 24 to 36 sq. ft.
1 gallon unit (3.79 liters) – 144 to 215 sq. ft.
- **Tarkett 930 Two-part Epoxy Nose Caulk Coverage:**
13.5 oz. cartridge, with #530 Caulking Gun at a 1/4" diameter bead – approximately 50 linear feet.
- **Tarkett 931 Rapid Reaction Epoxy Caulking Coverage:**
13.5 oz. cartridge, with #530 Caulking Gun at a 1/4" diameter bead – approximately 50 linear feet.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to vinyl nosing maintenance instructions for complete details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com

Contact Technical Support at (800) 899-8916 or E-mail:

Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139










800.899.8916

info@tarkettna.com

www.tarkett.com

Vinyl Nosings

Product Specification

Product Code	Profile	Description	Length Per Pc.	Pieces Per Ctn	Weight Per Ctn.
VDL XX RD Round Vinyl Stair Nosing		Double lock for butting to 1/8" tile or sheet goods	12 ft.	10	60 lbs.
VDL XX SQ Square Vinyl Stair Nosing		Double lock for butting to 1/8" tile or sheet goods.	12 ft.	10	73 lbs.
RCN XX A Recessed Vinyl Stair Nosing		Friction - grip nosing when only step is covered. Undercut for 1/4" and 5/16" carpet.	12 ft.	10	73 lbs.
RCN XX B Recessed Vinyl Stair Nosing		Heavy duty, with grooves and overlap lip. For 1/8" material with lip, 3/16" without lip.	12 ft.	10	69 lbs.
SRCN XX C For Thicker Carpeting on Steps.		For 3/8" Carpet on Step	12 ft.	4	60 lbs.
VIRCN XX A Visually Impaired Recessed Vinyl Stair Nosing		Nosing undercut for 1/4" to 5/16" carpet. 2" contrasting Visually Impaired strip.	12 ft.	6	67 lbs.
VIRCN XX B Visually Impaired Recessed Vinyl Stair Nosing		Heavy duty overlapping lip for 1/8" material with lip, 3/16" without lip. 2" contrasting Visually Impaired insert	12 ft.	10	62 lbs.
VIRCN XX B2 Visually Impaired Recessed Vinyl Stair Nosing		For 1/8" material. 2" Visually Impaired Grit Tape Insert	12 ft.	10	75 lbs.
VCD XX Double Undercut Carpet Stair Nosing		For 1/4" & 5/16" carpet. For step and riser, with ribbed surface.	12 ft.	10	76 lbs.

Tarkett North America

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139





800.899.8916

info@tarkettna.com

www.tarkett.com

Vinyl Nosings

Product Specification

Product Code	Profile	Description	Length Per Pc.	Pieces Per Ctn	Weight Per Ctn.
SVCD XX A For Thicker Carpeting on Step and Riser		For 3/8" Carpet on Step and Riser	12 ft.	4	60 lbs.
VIVCD XX Visually Impaired Double Undercut Stair Nosing		For 1/4" and 5/16" carpet for step and riser. 2" contrasting Visually Impaired strip.	12 ft.	5	55 lbs.
VITSN XX Visually Impaired Top Set Stair Nosing		Contrasting co-extruded strip. Top set on bare concrete, wood, steel.	12 ft.	10	50 lbs.
DTN XX Over/Top Stair Nosing		Top set residential stair nosing.	12 ft.	10	27 lbs.