

# R2900

**Lowry**  
The Tape Specialists

## POLYETHYLENE FILM SURFACE PROTECTION TAPE

### PRODUCT DESCRIPTION

This polyethylene surface protection film is primarily used to protect vinyl, stainless steel, aluminum, aluminum extrusions, UV painted surfaces, windows and doors, including textured and smooth painted surfaces.

It can also be used to protect semi-smooth surfaces such as hardwood and ceramic tile floors from dirt, spills, dust, construction debris, and damage. This polyethylene film is resistant to tears and punctures from sharp items. Ideal for use in high-traffic conditions in construction and renovation homes.

### PHYSICAL PROPERTIES

Backing:	LDPE
Colour:	Black & White
Adhesive:	Rubber based adhesive
Total Thickness:	75±5 micron
180°C Peel Strength:	320g / 25mm
Elongation at Break:	≥ 200%
Tensile Strength:	> 5MPa
Core I.D.:	3" (76mm±1)

### STANDARD WIDTHS

Custom widths available

### STANDARD LENGTH

500 feet (152.4 metres)

### RECOMMENDED STORAGE CONDITIONS

The product should be stored at room temperature and be kept away from wet and/or heat source.

The above properties and results obtained refer to the average values of laboratory testing carried out on the sample Lowry® product. Lowry® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. It is essential as with all pressure sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil. Lowry® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. Lowry® assumes no responsibility for any damage or injury sustained as a result of the use of its products.