

Tamayo 2224

Engineered Luxury Vinyl • Fresque

Benefits

Family friendly (including pet)

100% Waterproof
Ultra-durable wear layer with ceramic bead technology
Easy to clean
Stain resistant, including pet stains

Safe and healthy

Antimicrobial protective treatment to inhibit the growth of mold and mildew.
Phthalates-Free products meaning that they will not affect your quality of life
FloorScore® Certified for compliance with rigorous indoor air quality requirements
E1 Certified meaning that the product meets the European standard for indoor air quality
Made of virgin PVC (no recycled content) ensuring a uniform composition that doesn't contain any harmful substances.

Performant and durable construction

High-density rigid core vinyl planks (SPC)
Very sturdy - can withstand heavy furniture such as kitchen cabinets and islands
Performs in extreme temperatures (-4 to 122 °F / -20 to 50 °C)
Commercial abrasion resistance
BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards.

Easy maintenance

100% Waterproof
Antimicrobial, anti-mold and anti-fungal
Easy to clean
Stain resistant, including pet stains

Easy and versatile Installation

Floating installation
2 in 1 - comes with an attached underlayment
Can be installed in 3-season cottages (-4 to 122 °F / -20 to 50 °C)
No acclimation required
Compatible with embedded radiant heating
Can be installed on all floor levels
No telegraphing, even when installed over hard surface flooring
Minimal floor preparation
Installations of up to 4225 sq. ft. (65 linear ft.) in an open space without transition moldings
Matching moldings available

Quiet and comfortable

Foam backing for greater temperature and sound insulation
High soundproofing ratings (IIC/STC)

Notable look

Matte finish

Best-in-class Warranty

30 Days No Questions Asked Replacement

Quickship

Stock product for faster delivery

Tamayo 2224

Engineered Luxury Vinyl • Fresque

Product Specifications

Market Segments	Hospitality, Pro, Residential, Workspace
Sub Category	SPC
Collection	Fresque
Style Name	Tamayo
Style Number	2224
Construction	Engineered Luxury Vinyl
Format	Tile
Abrasion Resistance	General Commercial Use
Material	Virgin PVC
Core Material	70% Calcium Carbonate / 30% Virgin PVC
Width	12" (304.8 mm)
Total Thickness	0.197" (5 mm)
Wear Layer Thickness	0.0220" (0.5500 mm)
Core Thickness	0.1570" (4.0000 mm)
Backing	Ixpe Foam
Edges	4-Sided Micro Bevel
Locking System	Välinge 5Gi
Backing Thickness	0.0394" (1.0000 mm)
Finish	Travertine
Top Surface	UV-Cured Polyurethane & Ceramic Bead Technology
Gloss	High
Pattern Repeat	6
IIC	71
STC	71
Design	Concrete
Formaldehyde	E1
Vinyl Thickness	n/a
Length	24" (609.6 mm)
Certifications	FloorScore, E1 Certified, Phthalates-Free, BLC Certification, QuickShip, Virgin PVC
Installation Methods	Floating, Compatible with embedded radiant heating
	Rigid Engineered Luxury Vinyl Installation Guide - Välinge 5Gi
	Rigid Engineered Luxury Vinyl Installation Video - Välinge 5Gi Locking System



Warranties

- [Rigid Engineered Luxury Vinyl Warranty Guide](#)
- [Rigid Engineered Luxury Vinyl Maintenance Guide](#)

Residential use	No Questions Asked Replacement <i>30 days</i> Waterproof <i>Lifetime</i> Fade <i>Lifetime</i> Stain Resistance <i>Lifetime</i> Manufacturing Defects <i>Lifetime</i> Wear <i>Lifetime</i> Petproof <i>Lifetime</i>
Commercial use	Fade <i>15 Years</i> Wear <i>15 Years</i> Manufacturing Defects <i>15 Years</i> Stain Resistance <i>15 Years</i> Waterproof <i>Lifetime</i> Petproof <i>Lifetime</i>


Tamayo 2224

Engineered Luxury Vinyl • Fresque

Packaging information


Units Per Box	10
Boxes Per Pallet	66
Box Weight	33.20 pounds (15059.25 grams)
Square Meters Per Box	1.86
Square Meters Per Pallet	122.63
Square Feet Per Box	20
Square Feet Per Pallet	1320

Moldings




Flushmount Stair Nose - Round

Matching
94.488" X .984" X 2.834"
(2400 mm X 25 mm X 72 mm)



T-Molding

Matching
94.488" X 0.276" X 1.771"
(2400 mm X 7 mm X 45 mm)



Reducer

Matching
94.488" X 0.276" X 1.771"
(2400 mm X 7 mm X 45 mm)