

Aqua Mix® Grout Colorant



1. Product Name

Aqua Mix® Grout Colorant

2. Manufacturer

Custom Building Products
Technical Services
10400 Pioneer Boulevard, Unit 3
Santa Fe Springs, CA 90670
Customer Support: 800-272-8786
Technical Services: 800-282-8786
Fax: 800- 200-7765
Email: contactus@cbpmail.net
custombuildingproducts.com

3. Product Description

An easy-to-use, professional grade waterborne epoxy that recolors, seals and rejuvenates dirty or discolored existing grout joints. Use with a variety of grout types, including cement, epoxy, urethane and Single Component® grouts. Also simplifies ongoing grout cleaning by helping to guard against stains by sealing and protecting recolored grout. Includes Microban® antimicrobial protection that prevents the growth of stain-causing mold and mildew on cured colorant.

[Download Aqua Mix Grout Colorant Brochure](#)

Key Features

- Easy application and clean-up
- Durable epoxy formula
- Simplifies ongoing grout cleaning

Uses

- Sanded, unsanded, epoxy, urethane and single component grout joints.
- Effective for interior and exterior applications.

Benefits of Product in the Installation

- Excellent stain resistance
- Complies with all Federal EPA and SCAQMD standards for VOC

Limitations to the Product

- Grout Colorant is not recommended for use underwater in

- pools, ponds, or on areas subject to hydrostatic pressure.
- Do not use solvent-based cleaners, abrasive equipment or high-pressure washing equipment on recolored grout joints.
- Previously applied sealers, with the exception of [Aqua Mix® Penetrating Sealer](#), [Aqua Mix® Grout Sealer](#), [Aqua Mix® Pro-Solv](#), [Aqua Mix® Ultra-Solv®](#) or [Aqua Mix® Sealer's Choice® Gold](#), must be removed to provide a bondable surface. [Aqua Mix® Sealer & Coating Remover](#) is recommended for this procedure.
- Porous tile may require sealing to ensure colorant is not absorbed into the tile.

4. Instructions

General Surface Prep

Test a small area according to application instructions, with a minimum 1-hour cure time to determine desired results.

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Read entire label before using. SHAKE WELL before using. For new installations, Grout Colorant can be applied a minimum of 48 hours after grouting depending on jobsite conditions and ambient temperature. Grout joints must be clean, dry and free of existing sealers or coatings. Prepare existing grout joints:

MOST TILE & STONE: Use [Aqua Mix® Grout Colorant Pre-Treat Cleaner](#) or [Aqua Mix® Cement Grout Haze Remover](#).

ACID-SENSITIVE STONE OR SINGLE COMPONENT GROUT JOINTS: Use [Aqua Mix® Heavy-Duty Tile & Grout Cleaner](#).

EPOXY OR URETHANE GROUT JOINTS: Use [Aqua Mix® Sealer & Coating Remover](#).

If more than 1 bottle of a single color is to be used, mix the material together in a large container to ensure uniformity of color. Spread evenly using the Applicator Brush or toothbrush, working Grout Colorant into joint using a back-and-forth motion. Thin, even coats should be applied, limiting the amount of Grout Colorant that gets on the tile. If going from a dark to light grout color, more than 1 application may be necessary with a minimum 2-hours drying time between coats. After Grout Colorant has dried 1 or more hours (never more than 12 hours), lightly mist surface with water and let stand 5 minutes. Remove excess Grout Colorant from surface of tile using water and a white nylon scrub pad. Ready for surface traffic in 2 hours. Keep area dry for at least 24 hours. Avoid direct scrubbing on grout joints for 20 days to allow a full cure.

Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains styrene-acrylic copolymer. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention. KEEP OUT OF REACH OF CHILDREN.

5. Size & Availability

Location	Item Code	Color	Size	Package
USA	63001	White	8 oz (237 ml)	Bottle
USA	63002	Antique White	8 oz (237 ml)	Bottle
USA	63003	Linen White	8 oz (237 ml)	Bottle

Aqua Mix® Grout Colorant

USA	63004	Navajo	8 oz (237 ml)	Bottle
USA	63005	Buff	8 oz (237 ml)	Bottle
USA	63006	Sand	8 oz (237 ml)	Bottle
USA	63007	Beige	8 oz (237 ml)	Bottle
USA	63008	Wheat	8 oz (237 ml)	Bottle
USA	63009	Cinnamon	8 oz (237 ml)	Bottle
USA	63010	Cocoa	8 oz (237 ml)	Bottle
USA	63011	Light Gray	8 oz (237 ml)	Bottle
USA	63014	Black	8 oz (237 ml)	Bottle
USA	63015	Bright White	8 oz (237 ml)	Bottle
USA	63016	Canvas	8 oz (237 ml)	Bottle
USA	63017	Smoke	8 oz (237 ml)	Bottle
USA	63021	Silver	8 oz (237 ml)	Bottle
USA	63022	Natural Gray	8 oz (237 ml)	Bottle
USA	63023	Pewter	8 oz (237 ml)	Bottle
USA	63024	Charcoal Gray	8 oz (237 ml)	Bottle
USA	63025	Pure White	8 oz (237 ml)	Bottle
Canada	C063001	White	8 oz (237 ml)	Bottle
Canada	C063002*	Antique White	8 oz (237 ml)	Bottle
Canada	C063003	Linen White	8 oz (237 ml)	Bottle
Canada	C063004*	Najavo	8 oz (237 ml)	Bottle
Canada	C063005*	Buff	8 oz (237 ml)	Bottle
Canada	C063006*	Sand	8 oz (237 ml)	Bottle
Canada	C063007*	Beige	8 oz (237 ml)	Bottle
Canada	C063008	Wheat	8 oz (237 ml)	Bottle
Canada	C063009*	Cinnamon	8 oz (237 ml)	Bottle
Canada	C063010	Cocoa	8 oz (237 ml)	Bottle
Canada	C063011	Light Gray	8 oz (237 ml)	Bottle
Canada	C063014	Black	8 oz (237 ml)	Bottle
Canada	C063015*	Bright White	8 oz (237 ml)	Bottle
Canada	C063016	Canvas	8 oz (237 ml)	Bottle
Canada	C063017*	Smoke	8 oz (237 ml)	Bottle
Canada	C063021*	Silver	8 oz (237 ml)	Bottle

Canada	C063022	Natural Gray	8 oz (237 ml)	Bottle
Canada	C063023*	Pewter	8 oz (237 ml)	Bottle
Canada	C063024	Charcoal Gray	8 oz (237 ml)	Bottle
Canada	C063025	Pure White	8 oz (237 ml)	Bottle

* Indicates a special order item

All colors to match with all Custom Building Products grouting products are also available through special order.

Final installed shade may vary with the tile type, color and porosity as well as jobsite conditions and finishing techniques. For best results, perform a test on a small, inconspicuous area or create a sample board prior to installation.

6. Product Warranty

Custom® Building Products warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country or territory to another. For details and complete warranty information, visit the [Custom Building Products warranty page](#).

7. Technical Services Information

For technical assistance contact Custom® Building Products.

8. Filing System

Additional product information is available from the manufacturer upon request.