

Roberts[®] Carpet Seam Tapes

Premium tapes trusted for performance & easy glide formulation

Product Description

For more than four decades, flooring installers have turned to Roberts ® carpet seam tapes as the reliable solution for all residential and commercial carpeting installations. Roberts® tapes create robust seams for long-lasting floor coverings, with reduced smoke and odor.

Roberts® carpet seam tapes come with a variety of different widths, scrim designs, fiberglass reinforcement, and adhesive strengths, ensuring that there is a Roberts® seam tape with the right performance and at the right price for any carpeting installation.

Product	Description	Key Benefits	Application Type
50-500 MAX 500 Heat Bond Tape	 Carpet Seaming Tape 3-5/8" wide 22 yds. long 	 · 3" of scrim plus 2" of added fiberglass- reinforced scrim for the toughest jobs · Maximum layer of premium adhesives · Especially recommended for Berber carpet · Low smoke and low odor 	High traffic carpet applications – polyurethane-coated, polypropylene-backed, jute, Shaw Softbac [®] , woven
50-350 PREMIUM 350 Heat Bond Tape	 Carpet Seaming Tape 3-5/8" wide 22 yds. long 	 Extra thick layer of premium adhesive Stronger, quicker grab needed to seam deep- ribbed and coarse- backed carpets Low smoke and low odor 	High traffic carpet applications – polyurethane-coated, polypropylene-backed, jute, Shaw Softbac [®] , woven



50-11T MaxTrack Heat Bond Tape	 Carpet Seaming Tape 3-5/8" wide 22 yds. long 	 "Wide Track" center bead puts 80% more adhesive at center of seam to help prevent seam peaking and hinging Low smoke and low odor 	High traffic carpet applications – polyurethane-coated, polypropylene-backed, jute, Shaw Softbac [®] , woven
50-9T MaxTrack Heat Bond Tape	 Carpet Seaming Tape 3-5/8" wide 22 yds. long 	 "Wide Track" center bead puts 80% more adhesive at center of seam to help prevent seam peaking and hinging Low smoke and low 	Moderate traffic carpet applications – polyurethane-coated, polypropylene-backed, jute, Shaw Softbac [®]
		odor	Light traffic carpet applications – woven
50-340 XTRA 340 Heat Bond Tape	 Carpet Seaming Tape 3-5/8" wide 22 yds. long 	 Heavy woven fiberglass scrim provides extra stretch holding power Unique adhesive formulation provides extra adhesion, quick 	Moderate traffic carpet applications – polyurethane-coated, polypropylene-backed, jute, Shaw Softbac [®] , woven
		 • Low smoke and low • dow 	



50-315 DELUXE 315 Heat Bond Tape	 Carpet Seaming Tape 3-5/8" wide 22 yds. long 	 Premium features at a moderate price Effective in seaming a wide variety of carpets, including those with latex backings 	Moderate traffic carpet applications – polyurethane-coated, polypropylene-backed, jute, Shaw Softbac [®]
		· Low smoke and low odor	Light traffic carpet applications – woven
50-240 XT Heat Bond Tape	 Carpet Seaming Tape 3-5/8" wide 22 yds. long 	 High quality and economical Low smoke and low odor 	Light traffic carpet applications – polypropylene-backed, jute, Shaw Softbac [®]
50-360 ULTRA WIDE	 Carpet Seaming Tape 6" wide 22 yds. long 	 Heavy layer of adhesive and 6" width minimize seam peaking in all types of commercial installations Ideal for areas where cross lighting accentuates the seam Low smoke and low odor 	Recommended for the following carpet applications – polyurethane-coated, polypropylene-backed, jute, Shaw Softbac [®]
50-305	 "Step-on" Pressure Sensitive Tape 3-5/8" wide 5 yds. long 	 Perfect for temporary carpet repairs, or for use in difficult-to-seam, non-trafficked areas such as closets and behind toilets Does not require heat 	Light traffic carpet applications – polyurethane-coated, polypropylene-backed, jute, Shaw Softbac [®] , woven

* Low traffic application examples: bedrooms and lightly-used rooms in single-family homes or apartments

* Medium traffic application examples: hallways and heavily-used rooms in single-family homes or



apartments

* High traffic application examples: apartment building hallways, and all commercial applications (offices, hotels, hospitals, etc.)

gcpat.com | North America Customer Service: 1 877-4AD-MIX1 (1 877-423-6491)

This document is only current as of the last updated date stated below and is valid only for use in the United States. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.com. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

