Halex Concrete Flooring Nails

Concrete flooring nails are made with high carbon steel and hardened for maximum hold in the hard concrete substrates. Concrete flooring nails have been designed and tailored to the installer's specific needs for every type of flooring installation over concrete subfloors. All flooring nails are available in 50 lb bulk, 5 lb bags, and 1 lb bags.

General Purpose Concrete Flooring Nails

General purpose concrete flooring nails are used for most flooring installation applications. The 11/16 inch nail is the standard nail used as a pre-nail in carpet strip. Shorter lengths are used to install tap down style metal moldings when the nail heads will be covered by carpet. Longer lengths are used to install strip in special situations and are also used to temporarily hold carpet in position while seaming or stretching. All 12 gauge concrete flooring nails are also available with a rust resistant plated finish.

PRODUCT #	GAUGE	LENGTH (IN.)	APPROX. NAILS PER POUND
HN-108	12	1/2	760
HN-110	12	5/8	603
HN-111	12	11/16	557
HN-116	12	1	405

Heavy Duty Concrete Flooring Nails

Heavy duty concrete flooring nails are used with hard concrete when 12 gauge nails break or bend when driven. 5/8 inch nails and longer are also used to install carpet tack strips. Shorter concrete flooring nails are used to install metal molding when the nail heads will be covered by the carpet.

PRODUCT #	GAUGE	LENGTH (IN.)	APPROX. NAILS PER POUND
HN-208	10	1/2	335
HN-210	10	5/8	373
HN-212	10	11/16	320
HN-216	10	1	242

Extra Heavy Duty Concrete Flooring Nails

These extra heavy duty concrete flooring nails are used with very hard concrete that will not take a normal concrete flooring nail. They are slightly larger in diameter than a 1/8 inch drilled hole and are often used instead of aluminum drives or fluted concrete flooring nails. Nails over one inch long are used as stay nails. All extra heavy duty concrete flooring nails are plated for cleanliness and rust prevention.



PRODUCT #	GAUGE	LENGTH (IN.)	APPROX. NAILS PER POUND
HN-310	9	5/8	284
HN-312	9	3/4	238
HN-316	9	1	185
HN-324	9	1 1/2	128

Extra Heavy Duty Fluted Concrete Flooring Nails

These extra heavy duty concrete flooring nails are used with very hard concrete that will not take a normal concrete flooring nail. They are slightly larger in diameter than a 1/8 inch drilled hold and are often used instead of aluminum drives or fluted concrete flooring nails. Nails over one inch long are used as stay nails. All extra heavy duty concrete flooring nails are placed for cleanliness and rust prevention.

PRODUCT #	GAUGE	LENGTH (IN.)	APPROX. NAILS PER POUND
HN-410	9	5/8	284
HN-412	9	3/4	238
HN-416	9	1	185

Elasticel (Acoustical) Concrete Flooring Nail

These spiral shank flooring nails give extra holding power when driven into lightweight elasticel or acoustical concrete.

PRODUCT #	GAUGE	LENGTH (IN.)	APPROX. NAILS PER POUND
HN-120	12	1 1/4	384

gcpat.com | North America Customer Service: 1 877-4AD-MIX1 (1 877-423-6491)

This document is only current as of the last updated date stated below and is valid only for use in the United States. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.com. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.



Last Updated: 2018-08-24 gcpat.com/solutions/products/halex-concrete-flooring-nails