



SECTION 1. IDENTIFICATION

Product name : Sika® PowerSet Part A
 Other means of identification : No data available

Company name : 601, avenue Delmar
 Canada
 Pointe-Claire, QC H9R 4A9
 Sika Canada Inc.
 www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 3

Carcinogenicity (Inhalation) : Category 1A


Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure : Category 1 (Lungs, hearing organs)

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
 H335 May cause respiratory irritation.
 H350 May cause cancer by inhalation.



Precautionary Statements :

H351 Suspected of causing cancer.
 H361 Suspected of damaging fertility or the unborn child.
 H372 Causes damage to organs (Lungs, hearing organs) through prolonged or repeated exposure.

Prevention:

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use non-sparking tools.
 P243 Take action to prevent static discharges.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration \geq 1%.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS



Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Quartz (SiO ₂)	14808-60-7	Carc. 1A; H350i STOT RE 1; H372 STOT SE 3; H335	>= 40 - < 50
styrene	100-42-5	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Repr. 2; H361 STOT SE 3; H335 STOT RE 1; H372 Asp. Tox. 1; H304 Carc. 2; H351	>= 5 - < 10
Quartz (SiO ₂)	14808-60-7	Carc. 1A; H350i STOT RE 1; H372 STOT SE 3; H335	>= 30 - < 60
styrene	100-42-5	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Repr. 2; H361 STOT SE 3; H335 STOT RE 1; H372 Asp. Tox. 1; H304 Carc. 2; H351	>= 5 - < 10

|| Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	: Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and	: irritant effects carcinogenic effects



delayed	Cough Respiratory disorder May cause respiratory irritation. May cause cancer by inhalation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.
Notes to physician	: Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	: Water High volume water jet
Specific hazards during fire fighting	: Do not use a solid water stream as it may scatter and spread fire.
Further information	: Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharg-
---	--



es.

- Advice on safe handling : Do not breathe vapors or spray mist.
 Avoid exceeding the given occupational exposure limits (see section 8).
 Do not get in eyes, on skin, or on clothing.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Take precautionary measures against static discharge.
 Open drum carefully as content may be under pressure.
 Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
 Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Prevent unauthorized access.
 Store in original container.
 Keep in a well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Store in accordance with local regulations.
- Materials to avoid : Explosives
 Oxidizing agents
 Poisonous gases
 Poisonous liquids

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO ₂)	14808-60-7	TWA (Respirable particulates)	0.025 mg/m ³	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m ³	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m ³	CA QC OEL
		TWA (Respirable)	0.025 mg/m ³ (Silica)	CA BC OEL
		TWA (Respirable)	0.025 mg/m ³	CA BC OEL
		TWA (Respirable)	0.025 mg/m ³ (Silica)	CA BC OEL
		TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH



		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
calcium carbonate	471-34-1	TWAEV (total dust)	10 mg/m3	CA QC OEL
		TWA	10 mg/m3 (Calcium carbonate)	CA AB OEL
styrene	100-42-5	TWA	20 ppm 85 mg/m3	CA AB OEL
		STEL	40 ppm 170 mg/m3	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWA	35 ppm	CA ON OEL
		STEL	100 ppm	CA ON OEL
		STEV	100 ppm 426 mg/m3	CA QC OEL
		TWAEV	50 ppm 213 mg/m3	CA QC OEL
		TWA	20 ppm	ACGIH
		STEL	40 ppm	ACGIH

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-



Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove respiratory and skin/eye protection only after vapors have been cleared from the area. Remove contaminated clothing and protective equipment before entering eating areas.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: beige
Odor	: aromatic
Odor Threshold	: No data available
pH	: Not applicable
Melting point/range	: -30.4 °C
Initial boiling point and boiling range	: > 145 °C
Flash point	: ca. 31 °C (Method: closed cup)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: 7.7 %(V)
Lower explosion limit / Lower flammability limit	: 1 %(V)
Vapor pressure	: 6 hpa (20 °C)
Relative vapor density	: No data available
Density	: 1.65 - 1.75 g/cm ³ (20 °C)
Bulk density	: Not applicable
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-	: No data available



octanol/water Autoignition temperature	:	490 °C
		No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	> 60 mPa.s
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	37 g/l A+B Combined

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. Vapors may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.
Not classified based on available information.

Components:

styrene:

Acute inhalation toxicity : LC50 (Rat): 11.8 mg/l
Exposure time: 4 h
Test atmosphere: vapor

|| styrene:

Acute inhalation toxicity : LC50 (Rat): 11.8 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Skin corrosion/irritation

Not classified based on available information.



Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.
 Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.
 Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.
 May cause cancer by inhalation.
 Suspected of causing cancer.

IARC	Group 1: Carcinogenic to humans Quartz (SiO ₂) (Silica dust, crystalline)	14808-60-7
	Group 2B: Possibly carcinogenic to humans styrene	100-42-5
	Group 2B: Possibly carcinogenic to humans titanium dioxide	13463-67-7
OSHA	Not applicable	
NTP	Reasonably anticipated to be a human carcinogen styrene	100-42-5
	Known to be human carcinogen Quartz (SiO ₂) (Silica, Crystalline (Respirable Size))	14808-60-7

Reproductive toxicity

Suspected of damaging fertility or the unborn child.
 Suspected of damaging fertility or the unborn child.

STOT-single exposure

Not classified based on available information.
 May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Lungs, hearing organs) through prolonged or repeated exposure.
 Causes damage to organs (Lungs, hearing organs) through prolonged or repeated exposure.



Aspiration toxicity

Not classified based on available information.
Not classified based on available information.

Further information

Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution
Class : 3



Packing group : III
 Labels : Flammable Liquids
 Packing instruction (cargo aircraft) : 366
 Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1866
 Proper shipping name : RESIN SOLUTION
 Class : 3
 Packing group : III
 Labels : 3
 EmS Code : F-E, S-E
 Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

DOT: For Limited Quantity exceptions reference 49 CFR 173.150 (b)

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

TDG

UN number : UN 1866
 Proper shipping name : RESIN SOLUTION
 Class : 3
 Packing group : III
 Labels : 3
 ERG Code : 127
 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION
Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION
Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
 CA BC OEL : Canada. British Columbia OEL
 CA ON OEL : Ontario Table of Occupational Exposure Limits made under



	:	the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA ON OEL / STEL	:	Short-Term Exposure Limit (STEL)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value
ADR	:	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.



SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 02/27/2020
Prepared by : R & D of Sika Canada Inc.

Material number : 528825

||| <** Phrase language not available: [Z8] CUST - YMSDS-000000037 **>

CA / Z8