

Heterogeneous Project vinyl

eternal® de luxe

25 x 2 / 4 m

creating better environments

forbo
FLOORING SYSTEMS

eternal® de luxe

Realistic design for modern life

Rooted in Eternal's trusted expertise, Eternal de Luxe adds warmth, style, and superior acoustics to any environment. Its lifelike wood and stone designs create a welcoming, homely atmosphere which is beautiful, practical, and ready for everyday living and working.

Available in both 2m and 4m widths, Eternal de Luxe enables seamless installation. For smaller areas up to 40m^2, it can be installed adhesive free, making full recycling easy and straightforward.

A refined balance of design and function

The Eternal de Luxe collection sets a new standard in design, quality, and sustainability. With advanced in-register embossing techniques and refined natural patterns, it offers a realistic and contemporary flooring solution for modern interiors. Every detail has been developed to deliver lasting quality, visual authenticity, and environmental responsibility, creating a floor that performs.

Trusted performance

- **Enjoy quieter, more comfortable spaces,** thanks to a 17dB impact sound reduction achieved through the floor's 3mm construction, which also provides excellent underfoot support and ergonomic benefits.
- **Maintain lasting beauty,** with an advanced PUR finish that protects against scratches and wear.
- **Install with ease and confidence,** can be installed adhesive free up to 40m^2, offering flexibility without compromise.

Refined design

- **Experience the authentic look of real wood** with next-generation in-register embossing that follows the grain in two directions, creating remarkable depth and natural texture on both large and narrow plank designs.
- **Achieve a modern, balanced interior aesthetic** with the new narrower plank design, offering a refined and elegant look that complements contemporary spaces.
- **Bring natural realism into every space** through new matte embossing on stone designs, enhancing their tactile surface and delivering a subtle, true-to-nature appearance.

- **Available in 2m and 4m widths** for seamless installation.

Responsible choice

- **Contribute to a healthier indoor environment** with flooring made from over 50% natural raw materials, 18% recycled content, and is 100% phthalate-free.
- **Supports a more sustainable future,** when installed adhesive free the product can be fully recycled in line with the circular economy.
- **Choose a floor with a lower environmental impact** thanks to efficient production processes that minimise waste and maximise material reuse.

150 cm
16,66 cm



3087 | natural soft timber



3086 | light soft timber LRV 37



3087 | natural soft timber LRV 32



3089 | warm soft timber LRV 18

150 cm
20 cm



3034 | clear oak LRV 42



3036 | natural oak LRV 35



3028 | warm oak LRV 23



3028 | warm oak





3018 | whitewashed oak



3018 | whitewashed oak LRV 37



3016 | light honey oak LRV 36



3023 | greywashed oak LRV 33





3095 | pale elegant oak LRV 35



3092 | bleached elegant oak LRV 32



3093 | warm elegant oak LRV 23



3052 | golden oak



3052 | golden oak LRV 24



3024 | grey pine LRV 30



3117 | white neutral grey



3066 | mortar concrete LRV 34



3054 | greige concrete LRV 33



3117 | white neutral grey LRV 28



3111 | light neutral grey LRV 25



3096 | warm worn concrete



3096 | warm worn concrete LRV 36



3097 | grey worn concrete LRV 32

Technical specifications

Eternal de luxe meets the requirements of EN ISO 11638

18% RECYCLED CONTENT

100% RENEWABLE ELECTRICITY

PHTHALATE FREE

Total thickness	EN ISO 24346	3.0 mm
Surface finish		PUR Pearl
Wear layer thickness	EN ISO 24340	0.70 mm
Wear layer binder content	EN ISO 10582	Type 1
Collection size		20
Domestic use	EN ISO 10874	Class 23
Commercial use	EN ISO 10874	Class 33
Light industrial use	EN ISO 10874	Class 42
Roll width	EN ISO 24341	2.0 m / 4.0 m
Roll length	EN ISO 24341	≤ 25 m
Total weight	EN ISO 23997	2700 g/m²
Dimensional stability	EN ISO 23999	≤ 0.1 %
Slip resistance (ramp test)	DIN 51130	R10
Castor chair continuous use	ISO 4918	Pass
Residual indentation *Typical value*	EN ISO 24343-1	≤ 0.15 mm ~ 0.10 mm
Colour fastness to light	EN ISO 105-B02 method 3	≥ 6
Indoor air emissions: TVOC after 28 days	EN 16516	≤ 0.05 mg/m³
Acoustical impact noise reduction		17dB
Resistance to chemicals	EN ISO 26987	Very good
Flexibility	EN ISO 24344	Ø 10 mm
Use in wet areas	EN 13553	Yes
Life Cycle Assessment		LCA is the foundation for securing the lowest environmental impact
Creating better environments		
Renewable electricity		Eternal de luxe is manufactured using 100% electricity from renewable sources
Recycled content		Eternal de luxe contain up to 18% recycled content by weight
Black to the floor		Installation off cuts can be collected via our Back to the Floor scheme
SKA		Eternal de Luxe meets the Ska Rating criteria for M12 soft floor coverings in both office and retail schemes

Eternal de luxe meets the requirements of EN 14041:2004

Product code	EN 14041	0200403-DoP-306
Product code	BS EN 14041	0200403-DoP-GB306
Reaction to fire	EN 13501-1	B_{fl}-s1, L, CS
Slip resistance	EN 13893	μ ≥ 0.30
Thermal conductivity	EN 12524	0.25 W/mK
Body voltage	EN 1815	≤ 2.0 kV

RIBA · CPD CORE CURRICULUM

NBS Source
Manufacturing Partner

BACK TO THE FLOOR
RECYCLING PROGRAM

SAMPLE SERVICE
0800 731 2369
samples.uk@forbo.com

Forbo BIM
REVIT | ARCHICAD

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this samplebook are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, expressed or implied in respect of the information, content, materials or products displayed in this samplebook and does not represent that the information is accurate, complete or current and you are advised to visit our website at **www.forbo-flooring.co.uk** for up-to-date details or corrections to such contents.

LRQA CERTIFIED ISO 9001

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.
The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

Registered office:
Forbo Flooring UK Limited
High Holborn Road, Ripley
Derbyshire DE5 3NT
Registered in England 9200318

London EC1 showroom
79 St John Street, Clerkenwell
London EC1M 4NR
Tel: 0207 553 9300

For commercial enquiries
If calling from the North, London & South East
Tel: 0800 0282 162
If calling from Scotland, Midlands & South West
Tel: 0800 0935 258

Nuway enquiries:
Tel: 01773 740 688
Residential enquiries:
Tel: 0800 0935 846
E-mail: info.flooring.uk@forbo.com
www.forbo-flooring.co.uk

Ireland
Forbo Ireland Ltd
2 Deansgrange Business Park Blackrock
Co Dublin
Tel: 00353 1 2898 898
Email: info.ireland@forbo.com
www.forbo-flooring.ie

Find us on

creating better environments

FLOORING SYSTEMS

264226/022026