

MSI

Making Dream Surfaces Attainable



Brighton
Porcelain Collection
www.msisurfaces.com

Colors



Gold 12"x24"



Grey 12"x24"

Size	Thickness	GOLD	GREY
2x2	3/8"	NBRIGOL2X2HEX	NBRIGRE2X2HEX
12x24	3/8"	NBRIGOL1224	NBRIGRE1224
12x24P	3/8"	NBRIGOL1224P	NBRIGRE1224P
24x24	3/8"	NBRIGOL2424	NBRIGRE2424
24x24P	3/8"	NBRIGOL2424P	NBRIGRE2424P
24x48	3/8"	NBRIGOL2448	NBRIGRE2448
24x48P	3/8"	NBRIGOL2448P	NBRIGRE2448P

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	●	●	●	IV	V3	DCOF < 0.42 Polished DCOF > 0.42 Matte	> 275 lbf	< 0.5%	Matte 7 Polished 5
LIGHT COMMERCIAL	●	●	●						
HEAVY COMMERCIAL		●	●						

Freeze / Thaw	Chemical Resistance	Rectified / Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Rectified	Glazed

Elegant and classic, yet simultaneously modern, the Brighton Collection offers the beauty of natural marble with the solid performance of porcelain. Whether your style is traditional or contemporary, these tiles are a sophisticated addition to a kitchen, bathroom, living room, entryway, and more. Available in 12" x 24", 24" x 24", and 24" x 48" mosaic with bullnose accessories and colors ranging from cool white to bold black, the tiles complement a range of design styles.

Technical Information

Primary Colors: Gold, Grey
 Material Type: Glazed Porcelain
 Finish: Matte finish with texture
 Polished: Hardness / Mohs 5
 Matte: Hardness / Mohs 7

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Features At A Glance

- Uniquely Multi-Styled Contemporary to Rustic
- Glazed Porcelain
- Ink Jet Technology

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust. Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade.

Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.