

## Vinyl SPC Clic system

Physical properties	Specification
Product number	RVC748-XXXX
Width	7 inches (183 mm)
Lenght	48 inches (1220 mm)
Total thickness	5 mm
Wear layer thickness	0,30 mm
Top surface coating	Mat polyurethane with UV protection
Type of top surface	Deep emboss BP1
Click system locking	Unilin 5gi push- << Drop Lock >> system
Plank edges	Bevelled edge
ft2 per unit	2.4 ft2
ft2 per box	28.85 ft2
Planks per box	12 planks
Acoustic Underlayment Included	
Type	EVA
Thickness	1mm
Sound Transmission Class (ASTM E413-16)	STC 68
IIC ( <i>Impact Insulation Class</i> ) (ASTM E989-18)	IIC 66
Limited warranty	
Residential	25 years
Light commercial	10 years
Technical properties	
Percentage of virgin vinyl	100%
Percentage of recyclable materials	100%
Toxicity (ASTM F963-17)	Non toxic, no VOC's
Phthalates Content	Phthalates free
Abrasion/Wear Resistance (ASTM F510/F510M-14)	Average Value 2,8
Resistance to Chemicals (ASTM F3261-17) (ASTM F925-13)	0=no change
Resistance to heat (ASTM F3261-17)(ASTM F1514-03)	Average 0.65 (70°C)
Critical Radiant Flux (ASTM E648-19a)	>1.1 (W/cm <sup>2</sup> )
Slip resistance (ASTM D-2047-11)	Dry : 0.37
Reaction to fire - Flame/Smoke Spread	142 - 240
Peel Strength	ASTM D903-98(2017)
Dimensional Stability / Curling	ASTM F2199-09(2014)
Indoor Air Quality	FloorScore® Certified SCS-EC10.3-2014 v4.0