

MSI

Making Dream Surfaces Attainable



Antoni

Porcelain Collection

www.msisurfaces.com

Colors



Cafe 6"x36"

Gris 6"x36"

Nero 6"x36"

Platinum 6"x36"

Size	Thickness	CAFE	GRIS	NERO	PLATINUM
6X36 Matte	3/8"	NANTCAF6X36	NANTGRI6X36	NANTNER6X36	NANTPLA6X36

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	●	●	●	IV	V3	DCOF - > 0.42 Wet	> 275 lbf	< 0.5%	7
LIGHT COMMERCIAL	●	●	●						
HEAVY COMMERCIAL		●	●						

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Pressed	Glazed

Technical Information

Primary Colors: Black, Brown, Gray
 Material Type: Porcelain Glazed
 Finish: Matte

Features At A Glance

- Offered in a 6x36 for more traditional wood floor look
- Rectified wood planks allow for tighter grout joints
- Ink Jet technology creates a life like wood look with realistic textures

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.