

Custom**TECH**®

FLOORING PREPARATION SYSTEMS



NEW!

TechPatch™ SC

Standard Performance,
Skim Coat & Patching Compound

TechPatch SC is a fast-curing, cement-based, skim coat and patching compound that provides a smooth finish to a variety of substrates prior to the installation of floor coverings.

- Excellent for skim coat patching applications
- No additives required
- Apply from featheredge to 1/2" (13 mm)
- Install flooring in as little as 30 minutes



Scan this to learn
more about
TechPatch SC!



A DIVISION OF
CUSTOM®
A QUIKRETE® COMPANY

TechPatch™ SC

Standard Performance, Skim Coat & Patching Compound

A fast-curing, cement-based, skim coat and patching compound that provides a smooth finish to a variety of substrates prior to the installation of floor coverings. TechPatch SC helps eliminate installation problems of bond failure, crumbling, mildew and staining of resilient flooring due to free-moisture found in traditional underlayment. Its rapid setting formula allows installation of most floor coverings in as little as 30 minutes.

Suitable as an Underlayment for:

- Carpet
- Wood and parquet flooring
- Luxury Vinyl Tile/Planks (LVT/LVP)
- Vinyl composition tile (VCT)
- Sheet vinyl and rubber flooring
- Laminated flooring
- Ceramic, mosaic, quarry or cement body tile
- Impervious porcelain and glass tile
- Cement-based precast terrazzo
- Natural stone tile
- Terrazzo

Suitable Substrates*:

- Absorbent concrete
- Gypsum-based underlayment (meets ASTM F2419)
- Exterior grade plywood and OSB / APA or CANPLY Group 1
- Flooring manufacturer's approved wood underlayment
- Existing ceramic tile
- Resilient flooring
- Embossed vinyl
- Cutback adhesive residue
- Primed cement terrazzo
- Approved and prepared moisture control membranes

*Preparation and/or primers may be required to bond to any of these substrates

Benefits of Product in the Installation:

- Quick-setting formula permits floor covering installation in as little as 30 minutes
- Smooths the finishes on interior subfloors
- Patches and levels concrete and plywood from featheredge to 1/2" (13 mm)
- No additives required
- Compressive strength greater than 3000 psi

Ordering Information

ITEM CODE	SIZE	PACKAGE
TPSC10T	10 lb (4.5 kg)	Bag

Coverage

Typical square foot coverage per 10 lb. Bag (square meter per 4.5 Kg)

THICKNESS	SQUARE FEET		THICKNESS	SQUARE METER	
	MINIMUM	MAXIMUM		MINIMUM	MAXIMUM
SKIM COAT	100	300	SKIM COAT	9	27
1/8"	33.3	35.9	3.2 mm	3	3.3
1/4"	16.6	17.9	6.4 mm	1.5	1.6
1/2"	8.3	8.9	13 mm	0.7	0.8

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.



Warranty: Flooring Installation Systems products are backed by up-to a 25-year warranty. See CustomTechFlooring.com for full warranty information including limitations and exclusions.

©2024 Custom Building Products. All rights reserved. The CUSTOM® and CustomTech® logos, and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit customtechflooring.com for updated technical data sheets and SDS information.

Custom Building Products
800-272-8786
CustomTechFlooring.com
SS219 4/24N



A DIVISION OF
CUSTOM®
A QUIKRETE® COMPANY