

SAFETY DATA SHEET (SDS) / WB-2

Section 1 Product / Company Identification

Product Name Product Description Product Number Manufacturer & Address		WB-2 Acrylic Emulsin Solution 4510 DYNA Metro Inc. 37 Creditstone Road Concord, Ontario L4K 1N3 Canada
Manufacturer's Phone Number Manufacturer's Facsimile Date Of Issue Prepared By		+1 905.761.3309 +1 905.761.2114 June 5, 2018 Mark Gagro
Emergency Phone Numbers	Canutech Chemtrec	1-613-996-6666 (Canada) 1-800-424-9300 (U.S.)

Section 2 Emergency And First Aid

Emergency Information

Eyes	Rinse the eyes with a gentle stream of water for at least 15 minutes. Consult a physician immediately.
Skin	Remove contaminated clothing. Wash the skin with soap and water. Decontaminate or discard clothing. If irritation occurs, seek medical attention.
Inhalation	Remove from exposure and provide fresh air. If breathing has stopped, administer artificial respiration or oxygen as necessary. Consult a physician immediately.
Ingestion	Remove from exposure and provide fresh air. If breathing has stopped, administer artificial respiration or oxygen as necessary. Consult a physician immediately.



Section 3 Composition Information

Physical State	Liquid to semi-solid
Colour	Translucent clear yellow gel
Odour and Appearance	Viscouc liquid to semi-sold with acrylic odour
Water Solubility	Dilutable
Specific Gravity	1.1
Flash Point	100 Degrees C / 212 Degrees F
Freezing Point	0 Degrees C
Melting Point	Not applicable
Vapour Density (Air =1)	< 1
Vapour Pressure (mm Hg)	17 mm HG @ 20 Degrees C / 71 Degrees F
рН	8.5 - 9.5
Partition Coefficient (K o/w)	Not applicable
VOC	< 95 g/L

Section 4 Hazardous Ingredients

Ingredient Acrylic Polymer	CAS # Not Hazardous	OSHA PEL 48 - 52 %	ACGIHTLV-TWA	NOISH REL
Individual residual monomers	Not required	< 0.1 %		
Ammonia	7664-41-7	.02 % max		
Water	7732-18-5	48 - 52 %		



Section 5 Hazardous Identification

Respiratory Protection	None required if airborne concentrations are maintained below the TWA / TLV's listed in teh componenet Exposure Information Section. For airborne concetrations up to 10 times the TWA / TLV's listed in the Component Exposure Information Secion wear a MSHA / NIOSH approved half/mask, air purifying respirator.
Eye Contact	Chemical protective goggles. A face shield may be necessary.
Skin Contact	PVA, Viton and polyethylene gloves. Suitable of barrier materials shoudl be determined based on the use of this product. Protective clothing should be worn.
Ventilation	Local exhaust fants should be used to control the level of airborne contaminents. General dilution ventilation may assist in decution of airborne contaminants.
Other Equipment	Eye was station, safety shower.
Storage	Keep the material freezing: material may be coagulate.
Disposal Methods	Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supermatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, provincial, and federal regulations.
Labeling Requirements	This product is considered non-hazardous under the OSHA Hazzard Communication Standars (29CFR1910.1200)
	This product is not a controlled product under the Canadian Workplace Hazardous Material Information System (WHMIS).



Section 6 Accidental Release Measures

Spill Response Contain spill. Cover with absorbent material. Collect spilled material. Place in an approved metal container.

Methods of Disposal Incinerate in a permitted hazardous waste incinerator in the presence of a combustible material.

Section 7 Fire And Explosion

No
No
N/A
N/A
N/A
100°C
N/A

Section 8 Stability And Reactivity Data

Stability And Reactivity	Stable
Hazardous Polymerization	Will not occur
Conditions To Avoid	N/A
Incompatibility	There are no known materials which are incompatible.
Hazardous Decomposition	Thermal decomposition may yield acrylic monomers.
Reactivity	No



Section 9 Precautions For Handling And Storage

Storage Requirements	Keep container dry.
Incompatible Materials	Store away from acids or oxidizing agents . Store away from heat. Store out of direct sunlight.
Ventilation	Keep container in well ventilated area.
Fire Prevention	Ground containers securely when transferring contents. Wear low static or properly grounded shoes. No smoking while handling this material. Avoid shock or friction.
Explosion Prevention	Keep away from heat, sparks, open flame, and other sources of ignition. Prevent all sources of ignition. Vapours may ignite explosively.
	Avoid static discharge.
Static Prevention	Keep container tightly closed.

Section 10 Toxicological Information

 Accute Date
 The information shown in the Health Effect from Overexposure Section is based on the toxicity profiles for a number of acrylic emulsions that are compositionally similat to this product. Typical data are:

 Oral LF50-rat: > 5000 mg/kg
 Dermal LD50-rabbit : > 5000 mg/kg

 Skin irritation - rabbit : practically non-irritating
 Eye irritation - rabbit : inconsequential irritation

Section 11 Personal Protection / Exposure Control

Respiratory Protection:	Use local exhaust or general dilution ventilation to control dust levels below applicable exposure limits. Minimize dispersal of dust into the air.	
	If local or general ventilation is not adequate to control dust levels be- low applicable exposure limits or when dust causes irritation or dis comfort, use MSHA/NIOSH approved respirators.	
Eye Protection:	Wear safety glasses with side shields or goggles to avoid contact with the eyes. In extremely dusty environments and unpredictable environments, wear tight-fitting unvented or indirectly vented goggles to avoid eye irritation or injury. Contact lenses should not be worn when handling cement or cement containing products.	
Skin Protection:	Wear impervious abrasion- and alkali-resistant gloves, boots, long- sleeved shirt, long pants or other protective clothing to prevent skin contact. Promptly remove clothing dusty with dry Product or clothing dampened with moisture mixed with the Product, and launder before re-use. If contact occurs, wash areas contacted by material with pH neutral soap and water.	

Section 12 Personal Protection / Exposure Control

Disposal: Product As Product Pac Special Inst	ging No data available
---	------------------------



Section 13 Transportation Data

The Product is not hazardous under U.S. DOT or TDG regulations.

Section 14 Other Regulatory Information

Labelling RequirementsThis product is considered non-hazardous under the OSHA Hazard
Communication Standard (29CFR1910.1200)

This product is not a controlled product under the Canadian Workplace Hazardous Material Information System (WHMIS).

Section 15 Other Information

WHMIS Classification	N/A
IMO Description	N/A

