

DURA CONTRACT® - LVT

PRODUCT DESCRIPTION

1. Classification	ASTM F 1700-04 Class III, type B Solid Vinyl Floor Tile
2. Size	6" x 36", 9" x 48", 12" x 24", 18" x 18"
3. Overall Thickness	.098"/2.5mm
4. Wear Layer Thickness	20 mil/.50mm – Embossing: Smooth, Rustic, Sawcut, Liner
5. Construction	Multi Layered: 100% PVC, decorative film, Polyurethane wear layer.
6. Edge detail	Bevel or Square
7. Limited Wear Warranty	20-Year Residential / 10 Year Commercial
8. Recyclable Content	100% recyclable post-use

PRODUCT TESTING

1. Flammability	ASTM D 2859-06/CPSC FF 1-70	PASSED
2. Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥ 0.45
3. Smoke Density	ASTM E 662-06	<450
4. Slip Resistance	ASTM C 1028	Exceeds ADA & OSHA
5. Static Load Limit	ASTM F 970	1500 psi
6. Dimensional Stability	EN 434	$\geq 0.15\%$
7. Residual Indentation	EN433	$\geq 0.10\text{mm}$
8. Wear Resistance	EN660.2	<2.0mm ³
9. Fungus Test	ASTM G21:96	Grade 1, Passed
10. Toxic Element - VOC	EN71-3	Passed
11. Indoor Air Quality	FloorScore SCS-EC10.2 2007	Passed, FS-03340

