

**DIRECTIONS: KEEP OUT OF THE REACH OF CHILDREN. Always test product in an inconspicuous area to determine suitability for intended use. Suitability for a particular purpose is always the responsibility of the user.** 1) Make sure that the surface is thoroughly clean and free from waxes, sealants, or coatings of any kind. 2) Shake can well. Spray 10-16 inches from surface. Apply product evenly. Wipe off excess if spraying vertical areas. 3) Allow to cure for 24 hours. Test after application using water droplets, if droplets are absorbed, a second or third coat may be necessary to attain the desired performance. Dries to the touch in about one (1) hour at 75° F. **Use only in well ventilated areas. Open windows and use fans to circulate air. It is always recommended that gloves, goggles and a NIOSH approved respirator are worn at all times. HARMFUL OR FATAL IF SWALLOWED.**

**PRECAUTIONS:** Contains Aliphatic Hydrocarbons (8052-41-3), Acetone (67-64-1), N-Butane (106-97-8), Propane (74-98-6), Proprietary Polymer. Contents under pressure. Do not puncture, incinerate, or store above 120°F (49°C). **Product contains solvents. Keep away from heat, open flames, sparks and from possible ignition sources distant from application site. Do not smoke. Use only in well ventilated areas. Open windows and use fans to circulate air. It is always recommended that gloves, goggles and a NIOSH approved respirator are worn at all times. Keep adults, children and pets out of the area until product has thoroughly dried.**

#### **SUGGESTED FIRST AID PROCEDURES:**

**EYE CONTACT:** IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR APPROXIMATELY 15 MINUTES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

**SKIN CONTACT:** WASH AREA IN QUESTION WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

**INHALATION:** REMOVE PERSON TO FRESH AIR. IF SIGNS/SYMPTOMS PERSIST, CALL A PHYSICIAN.

**INGESTION:** DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

**WARRANTY:** Instructions on this label are a guide and should not be considered complete. In the event of failure, the only obligation shall be to replace such product proven defective. Neither seller nor manufacturer shall be liable for any injury or inability to use this product. It is the user's responsibility to ascertain the suitability, safety and toxicity of this product and assumes all liability and risk thereof. For more information, refer to the Material Safety Data Sheet available at: [www.benojgundlachco.com](http://www.benojgundlachco.com).



**No. GS02**

**SOLVENT BASED**

# **GROUT SEALER**

- **Spray-on application**
- **Can be applied immediately after grouting**
- **For use on walls, floors and countertops**
- **Does not change surface appearance**
- **Penetrates and seals grout**
- **20 year protection**

**PORCELAIN • CERAMIC • NATURAL STONE**

**No. GS02 Grout Sealer** is a VOC compliant solvent-based sealer that can be applied to damp/uncured grout immediately after grouting leaving no hard-to-remove residue and also works well on existing grout. It penetrates to protect grout, stone and masonry surfaces against oil and water-based stains.

#### **COVERAGE PER 15 oz. CAN:**

Linear Feet: 800 to 1000

Square Feet: 50 to 150

**PRECAUTION:** Surfaces which are not to be sealed must be protected with a masking material. Do NOT spray sealer onto acrylic or stained surfaces, such as cabinets, as this may cause discoloration.

**MAINTENANCE:** Clean treated areas with water and Gundlach pH Neutral Cleaner. DO NOT use harsh or abrasive cleaning agents on treated surfaces.

#### **EXPECTED WEAR UP TO 20 YEARS!**

This will vary depending on type of surface, wear and proper maintenance. This is not a warranty.

**In case of emergency call: 800-535-5053**

**KEEP AWAY FROM CHILDREN**

The contents of this aerosol are CFC free. Beno J. Gundlach Company is dedicated to preserving the environment.

For product information call:

TEL: 618 233-1781

[www.benojgundlachco.com](http://www.benojgundlachco.com)

