

SAFETY DATA SHEET (SDS)

PACT-III-80 – A

UNE MARQUE SIKA
A SIKA BRAND

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier: PACT-III-80 A
Other means of identification: None
Recommended use: Polyaspartic polyurea resin
Manufactured by: Parex Construction Chemicals Canada Inc.
 8320 Grenache
 Montreal, Quebec
 Canada H1J 1C5
Website: www.ctmfloorings.com
Prepared by: The health, safety and environmental department
Telephone number of preparers: 1-514-321-5540
Fax number: 1-514-321-5570
Emergency telephone number: **24-Hour Emergency Telephone Number Canada (CANUTEC):**
(613) 996 6666

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification of hazardous product

Flammable liquid (Category 2)
 Acute toxicity, Inhalation-mist (Category 4)
 Acute toxicity, dermal (Category 4)
 Aspiration Hazard (Category 1)
 Skin corrosion/irritation (Category 2)
 Serious eye damage/eye irritation (Category 2A)
 Skin Sensitization (Category 1)
 Specific target organ toxicity-single exposure (Category 3- respiratory system)
 Specific target organ toxicity – repeated exposure (Category 2)

GHS Label Elements

Hazard Pictograms/symbols



Signal word: DANGER

Hazard and Precautionary Statements

H225 Highly flammable liquid and vapour.
H332 Harmful if inhaled.
H312 Harmful in contact with skin.
H304 May be fatal if swallowed and enters airways.
H315 Causes mild skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

P210 Keep away from heat/sparks/open flames/ hot surfaces. No smoking. **P233** Keep container tightly closed. **P240** Ground/bond container and receiving equipment. **P241** Use explosion proof electrical/ventilating/lighting equipment. **P242** Use only non-sparking tools. **P243** Take action to prevent static discharge. **P280** Wear protective gloves/protective clothing/eye protection/face protection. **P261** Avoid breathing dust/fume/gas/mist/vapors/spray. **P271** Use only outdoors or in a well-ventilated area. **P264** Wash hands thoroughly after handling. **P272** Contaminated work clothing must not be allowed out of the workplace. **P284** In case of inadequate ventilation wear respiratory protection. **P304 + P340 IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **P312** Call a POISON CENTER/doctor if you feel unwell. **P305 + P351 + P338 IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **P337 + P313** If eye irritation persists: Get medical advice/attention. **P303 + P361 + P353 IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower. **P312** Call a POISON CENTER/doctor if you feel unwell. **P333 + P313** If



SAFETY DATA SHEET (SDS)

PACT-III-80 – A

UNE MARQUE SIKA
A SIKA BRAND

skin irritation or rash occurs: Get medical advice/attention. **P301 + P310 IF SWALLOWED:** Immediately call a POISON CENTER/doctor. **P331** Do NOT induce vomiting. **P370 + P378** In case of fire: Use foam, dry chemical, water fog or carbon dioxide (CO₂) to extinguish. **P362 + P364** Take of contaminated clothing and wash it before reuse. **P403 + P235** Store in a well-ventilated place. Keep cool. **P405** Store locked up. **P501** Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other Hazards Known: None known

GHS Special Labelling: EUH205 - "Contains epoxy constituents. See information supplied by the manufacture."

SECTION 3. COMPOSITION/INFORMATION OF INGREDIENTS

CHEMICAL NAME	CAS NUMBER	CONCENTRATION (%)
Aspartic ester	136210-32-7	25 - 50 %
Aspartic ester	136210-30-5	25 - 50 %
4-methyl-1,3-dioxolane-2-one	108-32-7	1 - 10 %
1-chloro-4-(trifluoromethyl)benzene	98-56-6	1 - 10 %
*Mixed xylenes	1330-20-7	1 - 10%
Ethyl benzene	100-41-4	1 - 5%
Dimethyl ester	616-38-6	1 - 10%

SECTION 4. FIRST AID MEASURES

- Inhalation** IF INHALED: Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.
- Ingestion** IF SWALLOWED: Seek immediate medical attention. Do NOT induce vomiting.
- Skin Contact** IF ON SKIN: Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.
- Eye Contact** IF IN EYES: In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.

Most important symptoms and effects (acute and delayed)

The most important known symptoms and effects are described in the labelling (section 2) and/or in section 11. Eye irritation, skin irritation, allergic symptoms. Symptoms may be delayed.

Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

General Information

If exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure the medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: In case of fire: Water fog, foam, dry chemical powder. Carbon dioxide (CO₂)

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this might spread the fire.

Specific hazards arising from the hazardous product: During fire, nitrous gases, fumes/smoke, isocyanates and vapour may be formed.

Combustion products may include: acidic hydrogen chloride & hydrogen fluoride, carbon oxide, hydrocarbons, nitrogen oxides and smoke

Special protective equipment and precautions for firefighting: Flammable. Evacuate area. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect personnel attempting to stop a leak. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Use water spray to cool fire exposed surfaces and to protect personnel. Self-contained breathing apparatus and turn-out gear must be worn in case of fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES



SAFETY DATA SHEET (SDS)

PACT-III-80 – A

UNE MARQUE SIKA

A SIKA BRAND

Personal precautions, protective equipment and emergency procedures

Isolate area. Keep unnecessary and unprotected personnel away. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillage cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental Precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat/sparks/open flames/ hot surfaces. – No smoking. Vapors may form explosive mixtures with the air. Provide suitable exhaust ventilation at the processing machines. Ensure thorough ventilation of stores and work areas. Avoid aerosol formation. When handling heated product, vapours of the product should be ventilated and respiratory protection used. Wear respiratory protection when spraying. Danger of bursting when sealed gastight. Protect against moisture. If bulging of drum occurs, transfer to well-ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate from acids and bases. Segregate from bases. Formation of CO₂ and build-up of pressure possible. Keep container tightly closed and in a well-ventilated place. Outage of containers should be filled with dry inert gas at atmospheric pressure to avoid reaction with moisture.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters (biological limit values or exposure limit values and source of those values)

Exposure limits:

CAS 136210-32-7	No exposure limits noted for the ingredient(s)				
CAS 136210-30-5	No exposure limits noted for the ingredient(s)				
CAS 108-32-7	No exposure limits noted for the ingredient(s)				
CAS 98-56-6	No exposure limits noted for the ingredient(s)				
CAS 616-38-6	No exposure limits noted for the ingredient(s)				
	<u>Form</u>	<u>Source</u>	<u>Limit/Standard</u>		
CAS 1330-20-7		OSHA Z1	TWA	435 mg/m ³	100 ppm
	Vapor	ExxonMobil	RCP-TWA	434 mg/m ³	100 ppm
		ACGIH	STEL	150 ppm	
		ACGIH	TWA	100 ppm	
CAS 100-41-4		OSHA Z1	TWA	435 mg/m ³	100 ppm
		ACGIH	TWA	20 ppm	

Engineering Controls

Provide good local exhaust ventilation to control vapour/mist. Eye wash facilities and emergency showers must be available when handling this product. Wash soiled clothing immediately. Contaminated equipment or clothing should be cleaned after each use or disposed of.

Personal Protective Equipment

Wear a NIOSH-certified (or equivalent) organic vapor/particulate respirator. Wear appropriate chemical resistant protective gloves. Wear tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists. Wear appropriate protective clothing. When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Eyewash fountains and safety showers are recommended in the work area.

SAFETY DATA SHEET (SDS)

PACT-III-80 – A

UNE MARQUE SIKA
A SIKA BRAND

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State/ Appearance/ Color:	Transparent liquid, Light yellow	Vapour Pressure:	Not available
Odour:	Aromatic	Vapour Density:	Not available
Odour threshold:	Not available	Relative Density:	1.064 (g/ml)
pH:	Not available	Solubility:	Insoluble in water
Melting/freezing point:	Not available	Partition coefficient-n-octanol/water:	Not available
Initial boiling point/range:	90°C /194°F	Auto-ignition temperature:	Not available
Flash point:	14.4°C (57.9°F)	Decomposition temperature:	Not available
Evaporation rate:	Not available	Viscosity:	300 - 400 cps
Flammability (solids and gases):	Flammable	VOC:	21.94 g/l
Upper and lower flammability/explosive limits	Lower 0.9% (V) Upper 12.9% (V)	Other:	None known

SECTION 10. STABILITY AND REACTIVITY

Reactivity: This product is stable and non-reactive under normal conditions of use, storage and transport. CAS 98-56-6 is dangerously reactive with strong oxidising agent, and produces a strongly exothermic reaction with sodium dimethylsulfinate.

Chemical Stability: This product is stable under normal conditions.

Possibility of hazardous reactions: Risk of bursting. Reacts with alcohols. Reacts with acids. Reacts with alkalies. Reacts with amines. Risk of exothermic reaction.

Conditions to Avoid: Keep away from heat, sparks and open flame. Avoid high temperatures. Avoid contact with incompatible materials.

Incompatible materials: Amines, alcohols, water, substances/products that react with polyureas.

Hazardous decomposition products: Thermal decomposition of CAS 98-56-6 produces hydrogen chloride and hydrogen fluoride.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely routes of exposure (inhalation, ingestion, skin and eye contact):

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Symptoms related to the physical, chemical and toxicological characteristics:

May cause allergic skin reaction with symptoms of reddening, itching, swelling, and rash. May cause skin irritation with symptoms of reddening, itching, and swelling. May cause eye irritation with symptoms of reddening, tearing, stinging, and swelling. May cause respiratory tract irritation with symptoms of coughing, sore throat and runny nose.

Delayed and immediate effects (chronic effects from short- term and long-term exposure):

Skin Sensitization – Sensitization after skin contact possible; **Respiratory Sensitization** – The substance may cause sensitization of the respiratory tract; **Germ Cell Mutagenicity** – Results could not be confirmed in tests with mammals; **Carcinogenicity** – A carcinogenic potential cannot be excluded after prolonged exposure to severely irritating concentrations. These effects are not relevant to humans at occupational levels of exposure; **Reproductive Toxicity** – No data available; **Specific Target Organ Toxicity – Single Exposure** – Causes temporary irritation of the respiratory tract; **Specific Target Organ Toxicity - Repeated Exposure** – The substance may cause damage to the olfactory epithelium after repeated inhalation; effect are not relevant to humans at occupational levels of exposure; **Aspiration Hazard** – No aspiration hazard expected; **Health Hazards Not Otherwise Classified** – No data available.

Numerical measures of toxicity (ATE; LD₅₀ & LC₅₀):

CAS 136210-32-7	LD ₅₀ , Oral - Rat >2000 mg/kg LD ₅₀ , Dermal – Rat >2000 mg/kg LC ₅₀ , Inhalation – Rat (aerosol) >4.224 mg/L, 4hr
CAS 136210-30-5	LD ₅₀ , Oral - Rat >2000 mg/kg LD ₅₀ , Dermal – Rat >2000 mg/kg LC ₅₀ , Inhalation – Rat (dust/mist) >4.224 mg/L, 4hr
CAS 108-32-7	LD ₅₀ , Oral - Rat >5000 mg/kg LD ₅₀ , Dermal – Rabbit >2000 mg/kg
CAS 98-56-6	LD ₅₀ , Oral- Rat – 6800 ² & 13000 mg/kg LC ₅₀ , Inhalation - Rat – 22000 & 33000 mg/m ³ LD ₅₀ , Dermal- Rabbit - >2000 mg/kg

SAFETY DATA SHEET (SDS)

PACT-III-80 – A

UNE MARQUE SIKA

A SIKA BRAND

CAS 1330-20-7 Inhalation Lethality: 4 hour(s) LC50 >20.0 mg/L (vapor) (Rat)
Oral Lethality: LC50 >3523 mg/kg (Rat)
Dermal Lethality: LC50 >4200 mg/kg (Rabbit)
CAS 100-41-4 Inhalation Lethality: 4 hour(s) LC50 17.8 mg/L (vapor) (Rat)
Oral Lethality: LD50 3.5 g/kg (Rat)
CAS 616-38-6 LD50, Oral- Rat - >5000mg/kg
LC50, Inhalation - Rat – > 5.36 mg/l, 4 hrs
LD50, Dermal- Rabbit - >5000 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and terrestrial information):

Hazardous to the aquatic environment

PRODUCT	SPECIES	RESULT
CAS 136210-32-7	EC50 scenedesmus subspicatus	113 mg/l - 72 h
CAS 136210-30-5	LC50 Danio rerio (zebra fish)	66 mg/l - 96 h
	IC50 scenedesmus subspicatus	113 mg/l - 72 h
	EC50 Daphnia magna (Water flea)	88.6 mg/l - 48 h
CAS 108-32-7	LC50 cyprinus carpio	> 1000 mg/l - 96 h
	EC50 Daphnia magna (Water flea)	> 1000 mg/l - 48 h
CAS 98-56-6	LC50 Lepomis macrochirus	5.6 mg/l – 96 h
	LC50 Lepomis macrochirus	11.4-14.1 mg/l – 72 h
	LC50 Salmo gairdneri	13.5 mg/l – 24 h
	EC50 Daphnia magna	3.7 & 5.6 mg/l – 48 h
	EC50 Daphnia magna	11.4 – 15.2 mg/l – 24 h
CAS 1330-20-7 / CAS 100-41-4	LC50 Oncorhynchus mykiss	2.6 mg/L - 96h
	EC50 Daphnia magna	1 mg/L – 24h
	ErC50 Pseudokirchneriella subcapitata	4.36 mg/L – 73h
	NOEC Oncorhynchus mykiss	>1.3 mg/L – 56days
	NOEC Daphnia magna	1.5 mg/L – 21days
	NOEC Pseudokirchneriella subcapitata	0.44 mg/L – 73h
CAS 616-38-6	EC50 Pseudokirchneriella subcapitata	>100 mg/l - 72 h
	EC50 Daphnia magna	>100 mg/l - 48 h
	LC50 Zebra danio	>100 mg/l - 96 h

Persistence and degradability: Not enough data available.

Bio accumulative potential: Not enough data available..

Mobility in soil: Not enough data available.

Other adverse effects: No data available.

SECTION 13. DISPOSAL CONSIDERATIONS

Information on safe handling for disposal/methods of disposal/contaminated packaging: Dispose of contents/container into safe container in accordance with local, regional or national regulations. Do not reuse empty container without proper cleaning. Do not heat or cut container with electric or gas torch.

SECTION 14. TRANSPORT INFORMATION

UN Number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations:

UN1263; PAINT RELATED MATERIAL; CLASS 3; PG II

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime):

UN1263; PAINT RELATED MATERIAL; CLASS 3; PG II

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air):

UN1263; PAINT RELATED MATERIAL; CLASS 3; PG II

Special Precautions (transport/conveyance): None known.



SAFETY DATA SHEET (SDS)

PACT-III-80 – A

UNE MARQUE SIKA
A SIKA BRAND

Environmental hazards (IMDG or other): None known.

Bulk transport (usually more than 450L in capacity): Possible

SECTION 15. REGULATORY INFORMATION

Safety/health Canadian regulations specifics: Refer to section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).

Environmental Canadian regulations specifics: Refer to section 3 for ingredient(s) of the DSL.

Safety/health/environmental outside regulations specifics: None

SECTION 16. OTHER INFORMATION

Date of latest revision of the safety data sheet:

4 MARCH 2021

Disclaimer:

NOTICE TO READER:

Parex Construction Chemicals Canada Inc expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages. All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Parex Construction Chemicals Canada Inc makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Parex Construction Chemicals Canada Inc's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

END OF S.D.S.