

STYLE INFORMATION

Total Thickness (mm)	5mm
Underlayment	No
Wear Layer (mm)	0.5mm
CE Certification	YES
Utilization Class	
Coating	UV coating
Embossing	BP surface
Bevelled	Micro - Bevel
Click	No
Fiberglass	Yes

PACK INFORMATION

Plank Size	187x1227mm (7.36"x48.31")
Plank per box	8
Sqm per Box	1.8357m ² (19.76 sq ft)

CERTIFICATE



TECHNICAL INFORMATION

Density	2000kg/m ³	
Dimensional Stability	X Direction: 0.05%	ASTM F2199-09
	Y Direction: -0.12%	
Effect of castor chair	No visible damage	EN425
Residual indentation	3%	ASTM F 1914-07
Impact Sound Insulation	60 dB	ASTM E2179-09
Light Fastness	≥6	ISO 105-B02
Slip Resistance	R10	DIN 51130
Chemical Resistance	Class 0	EN 423
	PASS	ASTM F 925
Curling after exposure to heat	-0.09mm	ASTM F2199-09
Fire Resistance	Bfl-S1	EN13501-1
	Pass	EN ISO 11925-2
	Pass	EN ISO 9239-1
Phthalates	Pass	CPSC-CH- C1001-09.3
Watertightness	N/A	EN13553
Wear Resistance	Group T	EN 660-2
Water Resistance	100%	
Burning cigarette test	Pass	ASTM E 662-15A
Toxic Element Test	Pass	EN 71-3
	Not toxic	
	Does not contain heavy metal and formaldehyde	