Safety Data Sheet ULTRABOND ECO 980

Safety Data Sheet dated: 06/10/2021 - version 5

Date of first edition: 11/14/2018

MAPEI

1. Identification

Product identifier

Mixture identification:

Trade name: ULTRABOND ECO 980

Other means of identification

Trade code: 1829

Recommended use and restrictions on use

Recommended use: Adhesive Restrictions on use: N.A. **Supplier's details**

Company: MAPEI INC. (Canada)

2900 Francis-Hughes Avenue H7L 3J5 - Laval - QC - CAN

Emergency phone number

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. Hazard identification



Classification of the product

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure if inhaled.

Suspected of causing cancer if inhaled, in contact with skin and if swallowed.

Label elements

Pictograms and Signal Words



Hazard statements:

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H351 Suspected of causing cancer if inhaled, in contact with skin and if swallowed.
 H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust or mist.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

Date 6/29/2021 Production Name ULTRABOND ECO 980 Page n. 1 of 9

P308+P313 IF exposed or concerned: Get medical advice/attention. P321 Specific treatment (see supplementary instructions on this label). P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. P362+P364 Take off contaminated clothing and wash it before reuse. P405 Store locked up. P501 Dispose of contents/container in accordance with applicable regulations.

Other hazards

None

Ingredient(s) with unknown acute toxicity

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

3. Composition/information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

List of components

Concentration (% w/w)	Name	Ident. Numb.	Classification	Registration Number
2.5-5 %	DIPHENYLMETHANE-2,4- DIISOCYANATE	CAS:5873-54-1	Eye Irrit. 2A, H319; Skin Irrit. 2, H315; STOT SE 3, H335; Resp. Sens. 1, H334; Acute Tox. 4, H332; STOT RE 2, H373; Skin Sens. 1, H317	
2.5-5 %	CALCIUM OXIDE	CAS:1305-78-8	Skin Irrit. 2, H315; STOT SE 3, H335; Eye Dam. 1, H318	
1-2.5 %	4,4'-METHYLENEDIPHENYL DIISOCYANATE	CAS:101-68-8	Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335; STOT RE 2, H373; Carc. 2, H351; Resp. Sens. 1, H334; Skin Sens. 1, H317	
0.25-0.49 %	Silica Sand	CAS:14808-60-7	STOT RE 1, H372; Carc. 1A, H350	
0.1-0.25 %	4-METHYLBENZENESULFONYL ISOCYANATE	CAS:4083-64-1	Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Resp. Sens. 1, H334	

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Date 6/29/2021 Production Name ULTRABOND ECO 980 Page n. 2 of 9

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke. Hazardous combustion products: N.A.

Explosive properties: N.A. Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

8. Exposure controls/personal protection

Control parameters

List of components with OEL value

Component	OEL Type	Country	Ceiling	Term	Term	Short Term	Term	Behaviour Note
				ma/m3	ppm	ma/m3	ppm	

 Date
 6/29/2021
 Production Name
 ULTRABOND ECO 980
 Page n. 3 of 9

DIPHENYLMETHANE-2,4- DIISOCYANATE	MAK	AUSTRIA		0,05	0,005	0,1	0,01	
CALCIUM OXIDE	OSHA			5				
	ACGIH			2				upper respiratory tract irritation;
	MAK	GERMANY		1				
	ACGIH			2				upper respiratory tract irritation
	MAK	AUSTRIA		1		4		
	MAK	SWITZERLAND)	2				
4,4'- METHYLENEDIPHENYL DIISOCYANATE	ACGIH				0,005			respiratory sensitization (listed under Methylene bisphenyl isocyanate (MDI));
	OSHA		С			0,2	0,02	
	MAK	GERMANY		0,05				
	ACGIH				0,005			respiratory sensitization (listed under Methylene bisphenyl isocyanate (MDI))
	MAK	AUSTRIA		0,05	0,005	0,1	0,01	
Silica Sand	ACGIH			0,025				A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;

Appropriate engineering controls

N.A.

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105: Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min. Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: paste Beige

Odour: Characteristic

Odour threshold: No data available

pH: 9.00

Melting point / freezing point: No data available
Initial boiling point and boiling range: 100 °C (212 °F)

Flash point: 100 °C (212 °F) Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: 1.1-1.2

Vapour pressure: No data available Relative density: 1.45 g/cm3 Solubility in water: soluble Solubility in oil: No data available

 Date
 6/29/2021
 Production Name
 ULTRABOND ECO 980
 Page n. 4 of 9

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available Oxidizing properties: No data available Solid/gas flammability: No data available

Other information

Substance Groups relevant properties No data available

Miscibility: No data available Fat Solubility: No data available Conductivity: No data available

10. Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

CALCIUM OXIDE a) acute toxicity LD50 Oral Rat = 500 mg/kg

4,4'- a) acute toxicity LC50 Inhalation Rat = 369 mg/m3 4h

METHYLENEDIPHENYL DIISOCYANATE

Silica Sand a) acute toxicity LD50 Oral Rat = 500 mg/kg

4- a) acute toxicity LC50 Inhalation Rat > 640 ppm 1h

METHYLBENZENESULFON

YL ISOCYANATE

LD50 Oral Rat = 2234 mg/kg

LD50 Oral Rat = 31600 mg/kg

If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure

Toxicological kinetics, metabolism

 Date
 6/29/2021
 Production Name
 ULTRABOND ECO 980
 Page n. 5 of 9

and distribution information

i) STOT-repeated exposure

j) aspiration hazard

Substance(s) listed on the IARC Monographs:

4,4'-METHYLENEDIPHENYL

Group 3

DIISOCYANATE

Silica Sand Group 1

Substance(s) listed as OSHA Carcinogen(s):

Silica Sand

Substance(s) listed as NIOSH Carcinogen(s):

Silica Sand

Substance(s) listed on the NTP report on Carcinogens:

Silica Sand

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

List of components with eco-toxicological properties

Component Ident. Numb. Ecotox Infos

CALCIUM OXIDE CAS: 1305-78-8 a) Aquatic acute toxicity: LC50 Fish Cyprinus carpio = 1070 mg/L 96h IUCLID

Silica Sand CAS: 14808-60-7 a) Aquatic acute toxicity: LC50 carp > 10000,00000 mg/L 72h

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. Disposal considerations

Safe handling and methods for disposal

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. Transport information

Not classified as dangerous in the meaning of transport regulations.

UN number

TDG-UN number: N.A. ADR-UN number: N.A.

Date 6/29/2021 Production Name ULTRABOND ECO 980 Page n. 6 of 9

DOT-UN Number: N.A. IATA-Un number: N.A. IMDG-Un number: N.A.

UN proper shipping name

TDG-Shipping Name: N.A.
ADR-Shipping Name: N.A.
DOT-Proper Shipping Name: N.A.
IATA-Technical name: N.A.
IMDG-Technical name: N.A.

Transport hazard class(es)

TDG-Class: N.A.

ADR-Class: N.A.

DOT-Hazard Class: N.A.

IATA-Class: N.A.

IMDG-Class: N.A.

Packing group

TDG-Packing Group: N.A. ADR-Packing Group: N.A. DOT Packing Group: N.A. IATA-Packing group: N.A. IMDG-Packing group: N.A.

Environmental hazards

Marine pollutant: No

Environmental Pollutant: N.A.

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions in connection with transport or conveyance

TDG:

TDG Special provisions: N/A Department of Transportation (DOT):

N.A.

Road and Rail (ADR-RID) :

N.A. Air (IATA) : N.A.

Sea (IMDG):

N.A.

15. Regulatory information

Canada - Federal regulations

DSL - Domestic Substances List

DSL Inventory:

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

NDSL Inventory:

No substances listed

NPRI - National Pollutant Release Inventory

Substances listed in NPRI:

No substances listed

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

DIPHENYLMETHANE-2,4- is listed in TSCA Section 8b Section 8a - PAIR

DIISOCYANATE

CALCIUM OXIDE is listed in TSCA Section 8b

4,4'-METHYLENEDIPHENYL is listed in TSCA Section 8b Section 8a - PAIR

DIISOCYANATE

Date 6/29/2021 Production Name ULTRABOND ECO 980 Page n. 7 of 9

Silica Sand is listed in TSCA Section 8b 4-METHYLBENZENESULFONYL is listed in TSCA Section 8b

ISOCYANATE

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

4,4'-METHYLENEDIPHENYL DIISOCYANATE

Section 313 - Toxic chemical list:

4,4'-METHYLENEDIPHENYL DIISOCYANATE

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

4,4'-METHYLENEDIPHENYL DIISOCYANATE Reportable quantity: 5000 pounds

CAA - Clean Air Act

CAA listed substances:

4,4'-METHYLENEDIPHENYL is listed in CAA Section 112(b) - HAP Section 112(b) - HON

DIISOCYANATE

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

Silica Sand Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

CALCIUM OXIDE

4,4'-METHYLENEDIPHENYL DIISOCYANATE

Silica Sand

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

CALCIUM OXIDE

4,4'-METHYLENEDIPHENYL DIISOCYANATE

Silica Sand

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

CALCIUM OXIDE

4,4'-METHYLENEDIPHENYL DIISOCYANATE

Silica Sand

16. Other information

Safety Data Sheet dated: 6/10/2021 - version 5

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description					
H315	Cause	Causes skin irritation.				
H317	May cause an allergic skin reaction.					
H318	Causes serious eye damage.					
H319	Causes serious eye irritation.					
H332	Harmi	ful if inhaled.				
Date	6/20/2021	Production Name	LILTRABOND ECO 980			

Date 6/29/2021 Production Name ULTRABOND ECO 980 Page n. 8 of 9

H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H351	Suspected of causing cancer.
H351	Suspected of causing cancer if inhaled, in contact with skin and if swallowed.
H372	Causes damage to organs through prolonged or repeated exposure.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

May cause damage to organs through prolonged or repeated exposure if inhaled.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

May cause damage to organs through prolonged or repeated exposure.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

H373

H373

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 6. ACCIDENTAL RELEASE MEASURES
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION

Date 6/29/2021 Production Name ULTRABOND ECO 980 Page n. 9 of 9