

Safety Data Sheet KERAFLEX RS GRAY

Safety Data Sheet dated: 10/16/2018 - version 1

Date of first edition: 10/16/2018

1. Identification

Product identifier

Mixture identification:

Trade name: KERAFLEX RS GRAY

Recommended use and restrictions on use

Recommended use: Polymer modified mortar

Restrictions on use: N.A. **Supplier's details**

Company: MAPEI INC. (Canada)

2900 Francis-Hughes Avenue H7L 3J5 - Laval - QC - CAN Phone: 1-450-662-1212

Emergency phone number

(USA) CHEMTREC 1-800-424-9300 (Canada) CANUTEC 1-613-996-6666

2. Hazard identification







Classification of the product

Skin Corr. 1A Causes severe skin burns and eye damage.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1 May cause an allergic skin reaction.

Carc. 1A May cause cancer if inhaled.

Carc. 1A May cause cancer if inhaled.

STOT SE 3 May cause respiratory irritation.

STOT RE 1 Causes damage to organs through prolonged or repeated exposure if inhaled.

Label elements

Pictograms and Signal Words



3

Hazard statements:

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H350 May cause cancer if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Date 10/16/2018 Production Name KERAFLEX RS GRAY Page n. 1 of 8

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a doctor.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment (see supplementary instructions on this label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up

P501 Dispose of contents/container in accordance with applicable regulations.

Other hazards

None

Ingredient(s) with unknown acute toxicity

None

3. Composition/information on ingredients

Substances

N.A

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

List of components

Quantity	Name	Ident. Numb.	Classification
25-50 %	Portland cement	CAS:65997-15-1	STOT SE 3, H335; Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Corr. 1A, H314
25-50 %	Silica Sand	CAS:14808-60-7	STOT RE 1, H372; Carc. 1A, H350
< 0,1 %	Lithium carbonate	CAS:554-13-2	Acute Tox. 4, H302; Eye Irrit. 2A, H319

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

Date 10/16/2018 Production Name KERAFLEX RS GRAY Page n. 2 of 8

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Explosive properties: N.A. Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

Always keep in a well ventilated place.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

8. Exposure controls/personal protection

Control parameters

List of components with OEL value

Component	OEL Type Country	Ceiling	Long Term mg/m3	Long Term	Short Term mg/m3	Short Term	Behaviour	Note
Portland cement	OSHA		15	FF		FF		
	OSHA		5					
	ACGIH		1					A4 - Not Classifiable as a Human Carcinogen;pulmonary function;respiratory symptoms;asthma;
Silica Sand	ACGIH		0,025					A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;

Appropriate engineering controls

N.A.

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Date 10/16/2018 Production Name KERAFLEX RS GRAY Page n. 3 of 8

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Solid

Appearance and colour: Powder grey

Odour: Cement like Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.
Initial boiling point and boiling range: N.A.

Flash point: N.A. Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.
Vapour pressure: N.A.
Relative density: 1.50 g/cm3
Solubility in water: Insoluble

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A.
Oxidizing properties: N.A.
Solid/gas flammability: N.A.

Other information

Substance groups relevant properties: N.A.

Miscibility: N.A. Fat Solubility: N.A. Conductivity: N.A.

10. Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

Silica Sand a) acute toxicity LD50 Oral Rat = 500 mg/kg

Lithium carbonate a) acute toxicity LC50 Inhalation Rat > 217 mg/l 4h

LD50 Oral Rat = 525 mg/kg

Date 10/16/2018 Production Name KERAFLEX RS GRAY Page n. 4 of 8

If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

Substance(s) listed on the IARC Monographs:

Silica Sand

Group 1

Substance(s) listed as OSHA Carcinogen(s):

Silica Sand

Substance(s) listed as NIOSH Carcinogen(s):

Silica Sand

Substance(s) listed on the NTP report on Carcinogens:

Silica Sand

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

List of components with eco-toxicological properties

Quantity Component

Ident. Numb. Ecotox Infos

25-50 % Silica Sand

CAS: 14808-60-7 a) Aquatic acute toxicity: LC50 carp > 10000,00000 mg/L 72h

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. Disposal considerations

Safe handling and methods for disposal

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. Transport information

Not classified as dangerous in the meaning of transport regulations.

UN number

TDG-UN number: N.A. ADR-UN number: N.A. DOT-UN Number: N.A. IATA-Un number: N.A. IMDG-Un number: N.A.

UN proper shipping name

TDG-Shipping Name: N.A.
ADR-Shipping Name: N.A.
DOT-Proper Shipping Name: N.A.
IATA-Technical name: N.A.
IMDG-Technical name: N.A.

Date 10/16/2018 Production Name KERAFLEX RS GRAY Page n. 5 of 8

Transport hazard class(es)

TDG-Class: N.A.
ADR-Class: N.A.
DOT-Hazard Class: N.A.
IATA-Class: N.A.
IMDG-Class: N.A.

Packing group

TDG-Packing Group: N.A. ADR-Packing Group: N.A. DOT Packing Group: N.A. IATA-Packing group: N.A. IMDG-Packing group: N.A.

Environmental hazards

Marine pollutant: No

Environmental Pollutant: N.A.

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A

Special precautions in connection with transport or conveyance

TDG:

TDG Special provisions: N/A Department of Transportation (DOT):

N.A.

Road and Rail (ADR-RID):

N.A.

Air (IATA):

N.A

Sea (IMDG):

N.A.

15. Regulatory information

Canada - Federal regulations

DSL - Domestic Substances List

DSL Inventory:

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

NDSL Inventory:

no substances listed

NPRI - National Pollutant Release Inventory

Substances listed in NPRI:

no substances listed

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

Portland cement is listed in TSCA Section 8b Silica Sand is listed in TSCA Section 8b Lithium carbonate is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

no substances listed

Section 304 - Hazardous substances:

no substances listed

Section 313 - Toxic chemical list:

Lithium carbonate

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

Date 10/16/2018 Production Name KERAFLEX RS GRAY Page n. 6 of 8

CAA - Clean Air Act

CAA listed substances:

no substances listed

CWA - Clean Water Act

CWA listed substances:

no substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

Silica Sand Listed as carcinogen

Lithium carbonate Listed as reproductive toxicant

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Portland cement Silica Sand

Lithium carbonate

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Portland cement

Silica Sand

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Portland cement

Silica Sand

Lithium carbonate

16. Other information

	Code	Description			
	H302	Harmful if swallowed.			
	H314	Causes severe skin burns and eye damage.			
	H317	May cause an allergic skin reaction.			
	H318	Causes serious eye damage.			
	H319	Causes serious eye irritation.			
	H335	May cause respiratory irritation.			
	H350	May cause cancer .			
	H350	May cause cancer if inhaled.			
	H372	Causes damage to organs through prolonged or repeated exposure .			
	H372	Causes damage to organs through prolonged or repeated exposure if inhaled			
C-f-t- D-t- Cht d-t-d- 10/16/2010					

Safety Data Sheet dated: 10/16/2018 - version 1

Product code: 9011917

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

Date 10/16/2018 Production Name KERAFLEX RS GRAY Page n. 7 of 8

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany. LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Date 10/16/2018 Production Name KERAFLEX RS GRAY Page n. 8 of 8